Low Power Linear Hall Sensor XL47Y

Features

- Wide linear range:0.8V~2.5V@V_{DD}=3.3V
- Low Operation Current: 1.0mA
- Wide Operating Voltage Range：2.7V~8V
- Zero-point (No magnetic field) output voltage:1.65V@V_{DD}=3.3V
- Sensitivity: 1.81mV/Gs@V_{DD}=3.3V
- Linearity: ±1%
- Low noise output without external capacitor filtering
- Temperature Grade 2: -40℃ to 105℃ Ambient Operating Temperature Range
- Device HBM ESD Classification Level Class3A
- DFN1616 package

Applications

- Game Handle
- Magnetic Axis Keyboards

General Description

The XL47Y is a linear Hall-effect sensor, featuring low power consumption, wide operating voltage, and extended temperature range, with an output voltage varies proportionally with the strength of the induced magnetic field, and its linear output voltage range follows the variation of the power supply voltage. The XL47Y's typical operating voltage is 3.3V, the default zero-point output voltage (without magnetic field) at V_{DD}=3.3V is 1.65V, with low operation current, the operating temperature range supports -40℃~105℃.

The XL47Y integrates high precision current source, temperature compensation module, Hall array, amplifier, driver module and other circuit modules, which provides high linearity and strong immunity to electromagnetic interference over the full voltage range and full temperature range.

Typical application schematic




Figure1.XL47Y Typical application schematic

Pin Configurations




Figure2.Pin Configuration of XL47Y

Table 1.Pin Description

Pin Number	Pin Name	Description
1	VDD	Supply Voltage Input Pin. XL47Y operates from 2.7V to 8V DC voltage
2,4,5	NC	No Connected
3	GND	Ground pin
6	OUT	Output Pin

Ordering Information

Order Information	Marking ID	Package Type	Eco Plan	Packing Type Supplied As
XL47Y	XL47Y	DFN1616	RoHS & HF	3000 Units Per Reel

Function Block




Figure3.Function Block Diagram of XL47Y

Absolute Maximum Ratings (Note 1)

Parameter	Symbol	Value	Unit
Input Pin Voltage	V_{DD}	−0.3 ~ 25	V
Output Pin Voltage	V_{OUT}	−0.3 ~ 25	V
Thermal Resistance (DFN1616) (Junction to Ambient, No Heatsink, Free Air)	R_{JA}	180	℃/W
Operating Temperature	T_A	−40 ~ 105	℃
Operating Junction Temperature	T_J	−40 ~ 125	℃
Storage Temperature	T_{STG}	−65 ~ 150	℃
Lead Temperature (Soldering, 10 sec)	T_{LEAD}	260	℃
ESD (HBM)	–	>4000	V

Note 1: Stresses greater than those listed under Maximum Ratings may cause permanent damage to the device. This is a stress rating only and functional operation of the device at these or any other conditions above those indicated in the operation is not implied. Exposure to absolute maximum rating conditions for extended periods may affect reliability.

XL47Y Electrical Characteristics (Note 2)

T_A = 25℃, V_{DD} = 3.3V, system parameters test circuit figure1, unless otherwise specified.

Parameters	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Operation Voltage	V_{DD}	–	2.7	3.3	8	V
Operation Current	I_{DD}	–	0.5	1.0	1.5	mA
Output Load Resistance	R_L	B=−1000Gs	20	–	–	kΩ
Output Voltage Range	$V_{OUT(H)}$	B=+1000Gs V_{DD}=3.3V	2.45	2.5	–	V
		B=+1000Gs V_{DD}=5.0V	4.15	4.2	–	V
	$V_{OUT(L)}$	B=−1000Gs V_{DD}=3.3V	–	0.8	0.85	V
		B=−1000Gs V_{DD}=5.0V	–	0.8	0.85	V
Static Output Voltage	$V_{OUT(Q)}$	B=0Gs V_{DD}=3.3V	1.567	1.65	1.733	V
		B=0Gs V_{DD}=5.0V	–	2.50	–	V
Linearity	Lin	–	−1	–	1	%
Output Settling Time	–	B=0Gs	–	0.2	–	μs
Output Noise	–	Bandwidth= 10Hz to 10kHz	–	0.8	–	mV

Note 2:

(1) Linearity is the degree to which the static characteristic curve between the input and output quantities deviates from a straight line.

(2) The output settling time is the time interval from when the output voltage begins to establish until it stabilizes at 90% of the steady−state output voltage.

XL47Y Magnetic Characteristics (Note 3)

Parameters	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Sensitivity	Sens	V_{DD}=3.3V	1.665	1.81	1.955	mV/Gs
		V_{DD}=5.0V	–	6.95	–	mV/Gs

Note 3:

(1) The magnetic South Pole (S) is defined as the positive magnetic field. The sensitivity in the table corresponds to measurements taken with the magnetic field perpendicular to the chip's marking surface.

(2) When V_{DD}=3.3V, the sensitivity corresponding to output voltage is in the linear range of 0.8V~2.5V as shown in the table. When V_{DD}=5.0V, the sensitivity corresponding to output voltage is in the linear range of 0.8V~4.2V as shown in the table.

Output Characteristics

T_A = 25℃, system parameters test circuit figure1, unless otherwise specified.




Figure4.Test Schematic of XL47Y




Figure5.XL47Y Output characteristic curve (V_{DD} = 3.3V)




Figure6.XL47Y Output characteristic curve (V_{DD} = 5.0V)

Note 4: At room temperature, when V_{DD}=3.3V, the linear range of chip unipolar is 0.8V~2.5V, when V_{DD}=5.0V, the linear range of chip unipolar is 0.8V~4.2V.





Figure7.Sensitivity versus temperature curve of XL47Y (V_{DD} = 3.3V)

Package Information

DFN1616



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	0.450	0.550	0.018	0.022
A1	0.000	0.050	0.000	0.002
A2	0.150 REF		0.006 REF	
b	0.200	0.300	0.008	0.012
D	1.550	1.650	0.061	0.065
D1	0.500	0.700	0.020	0.028
E1	0.900	1.100	0.035	0.043
E	1.550	1.650	0.061	0.065
e1	0.500 BSC		0.020 BSC	
L	0.190	0.290	0.007	0.011
k	0.260 REF		0.010 REF	

Important Notice

XLSEMI reserve the right to make modifications, enhancements, improvements, corrections or other changes without notice at any time. XLSEMI does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. XLSEMI assumes no liability for applications assistance or the design of Buyers' products. Buyers are responsible for their products and applications using XLSEMI components. To minimize the risks associated with Buyers' products and applications, Buyers should provide adequate design and operating safeguards. XLSEMI warrants performance of its products to the specifications applicable at the time of sale, in accordance with the warranty in XLSEMI's terms and conditions of sale of semiconductor products. Testing and other quality control techniques are used to the extent XLSEMI deems necessary to support this warranty. Except where mandated by applicable law, testing of all parameters of each component is not necessarily performed.

For the latest product information, go to www.xlsemi.com.